



(19)

(11) Publication number:

60105508 A

Generated Document.

PATENT ABSTRACTS OF JAPAN(21) Application number: **58213848**(51) Intl. Cl.: **B29C 39/24**(22) Application date: **14.11.83**

(30) Priority:

(43) Date of application
publication: **11.06.85**(84) Designated contracting
states:(71) Applicant: **TOKYO SEAT KK**(72) Inventor: **MIYAZAKI MASAHIRO
SHIBATA TAMOTSU
YOSHIMURA HITOO**

(74) Representative:

**(54) PREPARATION OF
INTEGRALLY BLOW-
MOLDED PIECE**

(57) Abstract:

PURPOSE: To prepare voidfree pad material by a method wherein resin flow in a blow mold is adjusted by a U type baffle plate and the corner sides of a mold cover member.

CONSTITUTION: The U type baffle plate 5 is inserted previously into the cover member. Foam material is injected gradually into the cover

member 1 and expanded. Then, the flow of the foam material 8 is moved forcedly by the U type baffle plate 5 toward the corner part 3a of the rise part. Stagnant expanded gas is extruded by the forced adjustment not to produce voids 4'. In this manner, the pad material 4 free from defects such as voids etc. can be provided.

COPYRIGHT: (C)1985,JPO&Japio

